

## K990



### ➔ Standalone RFID Time & Attendance with Access Control

Card Capacity : 30,000  
 Transaction Storage : 1,00,000  
 Card Reader : Yes  
 CPU : 32 bit Microprocessor - 800Mhz  
 FAR :  $\leq 0.0001\%$  / FRR :  $\leq 1\%$   
 Identification Speed :  $\leq 0.1$  sec  
 Display : 3.5" TFT  
 Keypad : 4 x 4 with 5 function Keys  
 Schedule Bell/Speaker : Mini Speaker  
 Communication : RS232/485, TCP/IP  
 Push data : Yes  
 Standard Features : Work code, SMS, DLST,  
 Self service query, Status Switch  
 Power Supply : 12V DC , 1.5Amp  
 Operating Temperature : 0°C to 45°C  
 Operating Humidity : 20% -80%  
 Dimension : 212 x 159 x 45 mm  
**Access Control** : Wiegand : In & Out  
 both 26 or 34 bit (With or without site code)

Relay : 12 V relay for lock EM lock,  
 Bolt Lock or Strike lock  
 Support Fire Alarm : Yes / Door Sensor ; Yes  
 Anti Passback : Yes / Door Bell : Yes  
 Support exit reader : KR 500E, KR503, 101HE and  
 50 time zones, 5 group, 10 time combination  
 Battery : Yes / Card Readers : Yes  
 Communication : Wifi/GPRS  
 Printer : Yes

#### **Compatibility :**

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

#### **Compatible Software & SDK :**

- Smart office suite desktop and web
- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications