



## Multibio 800-H

### ➔ Multi-biometric Access Control and Time Attendance System

Face capacity : 1500(1:N)  
Fingerprints templates : 1000  
Card Storage : 1000(Optional) ID  
Transaction storage : 1,00,000  
Card reader : Yes  
CPU : 800 Mhz 32 bit Microprocessor  
Fingerprint sensor : 500 DPI Optical sensor  
FAR :  $\leq 0.0001\%$   
FRR :  $\leq 1\%$   
Identification speed :  $< 0.5$  sec  
Algorithm Ver : 10  
Display : 2.8 inch TFT LCD Color Screen  
Keypad : 4 x 4 with 5 function Keys  
LED Indicator : Green/Red  
Schedule Bell/Speaker : Mini Speaker  
Communication : TCP/IP, RS232/485, USB Host  
Push data : No  
Power Supply : 12V DC, 3A  
Operating Temperature : 0 °C - 45 °C  
Operating Humidity : 20% - 80%  
Wiegand : IN / OUT

Relay : 12 V relay for lock EM lock, Bolt Lock or Strike lock

Support Fire Alarm : Yes

Door Sensor : Yes

Anti Passback : Yes

Door Bell : Yes

Support exit readers : No

Battery : No | Communication : No

Sensor : No

#### Compatible :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)
- Support External Printer

#### Compatible Software and SDK:

- Smart office suite desktop and web
  - etime track lite desktop & web
  - SDK for desktop applications
  - Web based Device Manager/ePush server using Push data.
- Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications