



Vertical type - TS1000 series:

TS1000	TS1011	TS1022
Tripod Turnstile	RFID	FP + RFID

➔ TS1000 - Oneway vertical tripod turnstile

Type : Vertical Tripod
 Arm Length : 50cm
 Max tolerance of Arms : 80 Kg
 Angle per rotation : 120 Degree
 Operation Type : Oneway - Bidirectional
 Flow Rate : 25-48 passages/minute
 Input control signal : Dry contact
 Ingress protection Degree : IP54
 Opening Duration : 5s - 60s
Hardware & Interface :
 Primary controller (Inbuilt)
 CPU : 32 bit Microprocessor
 Opening Signal Input : yes
 Emergency Switch Input : yes
 Direction Indicator Output : yes
 Passing Indicator Output : Yes
 Drop Arm Electromagnet Output : Yes
 Secondary Controller : No

Optional Interface :

Any Standalone access controller system
 Eg. X990, IFACE, SC403,X7,SF101,F702 etc.

Power Supply :

SMPS - Input : AC 220V / 110V, 50Hz / 60Hz

SMPS - output : DC +24V, 5A; +12V, 3A

Dimension(mm) : L = 520, W = 280, H = 980

Gross Weight : 40kg

Operating Temperature : -28°C to +60°C

Operating Humidity : 5% - 85%

Operating Environment : Indoor & Outdoor(shelter)

Dimension :(All units in mm)

