



VF380

➔ **Multibiometric Identification Time Attendance & Access Control System**

Face Capacity : 800
Card Capacity : 10,000
Transaction storage : 1,00,000 logs
Card Reader : Yes
Image Sensor : Special Sterio Dual Sensor
FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
Identification Speed : ≤ 1 Sec
Algorithm Ver : NA
Display : 3" TFT Screen
Schedule Bell/Speaker : Mini Speaker
Communication : TCP/IP , USB- Host
Camera : High Resolution Infrared Camera
Standard Features : Automatic Status Switch,
Self Service Query Work code
Power Supply : 12V DC, 1.5 Amps
Operating Temperature : 0°C to 45°C
Operating Humidity : 20% -80%
Dimension : 104.70 x 160.00 x 36.00 mm

Access Control :

Wiegand : No
Relay : 12 V
Support Fire Alarm : Yes / Door Sensor ; Yes
Anti Passback : No / Door Bell : Yes
Support exit reader : No
Battery : No / Card Readers : Yes
Communication : No
Printer : No

Compatibility :

- Door Sensor, EM Lock

Compatible Software & SDK :

- Smart office suite desktop and web
- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using
Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP
and Other applications