



inBio-260 Pro

➔ Multidoor Access Control - 2 Door

Number of doors controller : 2 Door
 Numbers of readers supported : 8 (4 RS-485 Reader, 4 26-bit wiegand reader)
 Types of readers supported : 26-bit Wiegand & RS485 FR Series Reader
 Number of Inputs : 6(2 Exit Device, 2 Door Status, 2 AUX)
 Number of Outputs : 4 (2-Form C Relay or Lock & 2-Form C Relay for Aux Output)
 Card holders Capacity : 60,000
 Fingerprint Capacity : 20,000
 Log Events Capacity : 100,000
 Communication : TCP/IP and RS-485
 Push Data (centralization)
 Enclosure : Metal Box
 Mounting : Wall Mount
 Package Dimension : 350(L)×90(H)×300(W)mm
 Package Weight : 3.6kg | CPU : 32 bit 1.2GHz CPU
 Ram : 128MB : Flash Memory : 256MB
 Power : 12VDC, 3/3.5A
 Operating Temp : 0-45 °C
 Operating Humidity : 20% to 80%

Features:

- Embedded Fingerprint verification and advance Anti-pass back function
- support TCP/IP and RS485 communication
- access control function
- 256 time Zones, 256 access levels
- Data is preserved if power is lost, Controller continues to operate if data connection is interrupted
- Multi-Card Opening function, Remote door opening and closing
- Real-Time monitoring Via Web browser
- 2 auxiliary input can be connected to infrared body, Detectors, Fire alarms, smoke detectors etc.
- 2 auxiliary output can be connected to alarms, cameras, door bells, light indicator etc.
- Global Anti-pass back, Global Interlock and Global Linkage
- Who is inside
- Alarms and Events Notifications through Email
- Supports Video Integration & Visitor Management Module

Software and Database Supported:

- Bio Security 3.0 (Web based application)
- PGSql by default, Supported MSSQL 2005/2008/2012 and Oracle 11g enterprise edition.