

inBio 460



➔ Multidoor Access Control - 4 Door

CPU : 32bit MIPS CPU

RAM : 32MB

Flash Memory : 128 MB

Fingerprint Capacity : 3000

Card Capacity : 30,000

Event buffer : 1,00,000

Power / Current : 12V +5A for Controller

Communication : RS485 , TCP/IP

Numbers of readers supported : 12 (8 RS-485

Reader, 4 26-bit wiegand reader)

Types of readers supported : 26-bit Wiegand and
RS485 FR Series Reader

Number of Inputs : 12(4 Exit Device,
4 Door Status, 4 AUX)

Number of Outputs : 8 (4-Form C Relay or Lock
and 4-Form C Relay for Aux Output)

Supports : F12 (RS 485) Fingerprint Reader

Software and Database Supported :

Access Security System 3.5 (Desktop Version)

Database Type:- MS Access / MS SQL

Features:

- 256 time Zones, 256 access levels
- Anti-passback function
- It can be installed easily on your network also support TCP/IP and RS485 communication
- 1/2/4 Door models can be mixed and matched in an optimised System Architecture
- Data is preserved if power is lost, Controller continues to operate if data connection is interrupted
- Interlock function , Linkage function
- Multi-Card opening function,
Remote door opening & closing
- Real-Time monitoring via web browser
- Video server integration
- 4 auxiliary input may be connected to infrared body detectors, fire alarms, smoke detectors etc.
- 4 auxiliary output may be connected to alarms, cameras, door bells etc.
- Supports : eSSL 5000 / 7500 for fingerprint registration